



















# GENERATING SET GE 12054 HBS



## FEATURES

- Engine shut down for low oil level
- Automatic voltage regulator "AVR"
- Sockets : 1x400V 16A 3P+N+T CEE IP67- 2x230V 16A 2P+T SCHUKO
- Isometer
- Circuit breaker
- Protective frame
- Meets EC directives

The images are for reference

Standard Equipment										
	Petrol engine	Air cooling	Electric Starter	Battery 12V	Oil pressure Indicator	Engine shut down (oil)	Hours-meter			
										
	Synchronous alternator	Automatic voltage regulator	Sockets	Sockets	Isometer	Circuit breaker	Thermal shut off	Voltmeter		
	Options on request		• Earthing kit		• Hand trolley CTM10					

## Technical data

## GE 12054 HBS

**A.C. GENERATION - 50 Hz - Three-phase synchronous alternator, self-excited, self-regulated, brushless**

* Stand-by three-phase power	13 kVA (10.4 kW) / 400V / 18.7A
* PRP three-phase power	12 kVA (9.6 kW) / 400V / 17.3A
* PRP single-phase power	6 kVA/ 230 V / 26 A
Cos φ	0.8
Insulation class	H

\* Output powers according to ISO 8528-1

**ENGINE - 4-stroke petrol, OHV, Air cooling**

Model	HONDA GX 630
* Stand-By net power	14.5 kW (19.7 HP)
* PRP net power	10.5 kW (14.3 HP)
Cylinders/ Displacement	2/ 688 cm <sup>3</sup>
Speed	3000 rpm
Fuel consumption (75% of PRP)	3.9 l/h

Potenze dichiarate in accordo a SAE J1346

## GENERAL SPECIFICATIONS

Tank capacity	18 l
Running time (75% of PRP)	4.5 h
IP protection degree	IP 54
*Dimensions LxIhx (mm)	935x525x645
*Dry weight	160 kg
**Acoustic power LwA (pressure LpA)	99 dB(A)(74 dB(A) @ 7m)

\* Dimensions and weight without trolley/trailer. / \*\*For fixed installation only in the EU market

Mosa reserves the right to change this specification without notice. For further information please contact the sales department.