



# GENERATING SET GE SX-11000 KDT

The images are for reference



## FEATURES

- Control panel with digital control unit
- Automatic voltage regulation "AVR"
- Four pole circuit breaker
- ELCB-GFI (Ground Fault Interruptor)
- Bundled base suitable to contain any liquids leakage from engine avoiding environmental pollution
- Central lifting eye
- The rounded edges of the canopy designed for rainwater drainage away
- Canopy with large opening to allow easy maintenance (replacement of air, oil, fuel filters)
- Central lifting eye
- Large fuel tank
- Fuel level sensor
- External plugs for oil and water drainage
- Emergency stop button
- Prepared for remote Start and Stop control
- Prepared for connection to PAC-I switching panel (ATS)
- Low noise level
- Meets EC/UE directives



water cooled



diesel



three-phase



electric start

## POWER RATINGS

* Stand-By three-phase power (LTP)	11 kVA (8.8 kW) / 400V/15.9A
* PRP three-phase power	10 kVA (8 kW) / 400V/14.4A
* PRP single-phase power	7 kVA/kW / 230V/30.4A
Frequency	50 Hz
Cos φ	0.8

\* Powers declared according to ISO 8528

## DEFINITION

Valid declared powers up to the followings environmental conditions: temperature 25°C, altitude 100 meters above sea level)

**LTP power: stand-by power:** Maximum available power for use with variable loads for a yearly number of hours limited at 500 h. No overload is admitted.

**PRP power:** continue power with variable loads. Maximum power for use with variable loads for a yearly illimited nubers of hours.

**COP power:** continuous power with constant load. Maximum power for use with constant loads for a yearly unlimited numbers of hours.

## ENGINE 3000 RPM

### 4 STROKE, NATURAL ASPIRATED

Model	KOHLER KDW702
Stand-By net power	10.3 kW (14 hp)
PRP net power	9.3 kW (12.6 hp)
COP net power	/
Cylinders / Displacement	2 / 686 cm <sup>3</sup> (0.686 lt.)
Bore / Stroke	75 / 77,6 (mm)
Compression ratio	22.8 :1
BMEP (Brake Mean Effective Pressure : LTP - PRP)	/
Speed governor type	Mechanical
<b>FUEL CONSUMPTION</b>	
110 % (Stand-by power)	3.9 lt./h
100 % to PRP	3.4 lt./h
75 % to PRP	2.6 lt./h
50 % to PRP	1.9 lt./h
<b>COOLING SYSTEM</b>	
Total system cap. - only engine	lt - 1.1 lt
Fan air flow	72 m <sup>3</sup> /min.
<b>LUBRICATION SYSTEM</b>	
Total oil system capacity	/
Oil capacity in sump	1.6 lt
Oil consumption at full load	/

## EXHAUST SYSTEM

Maximum exhaust gas flow	2.2 m <sup>3</sup> /min.
Max. exhaust gas temp.	540 °C
Maximum back pressure	6000 kPa (0.06 bar)
External diameter exhaust pipe	/
<b>ELECTRICAL SYSTEM</b>	
Starter motor power	1.6 kW
Battery charging alternator cap.	40 A
Cold start	- 15 °C
With cold start aid	/
<b>AIR FILTER</b>	
Combustion air flow	1.02 m <sup>3</sup> /min.
<b>HEAT REJECTED AT FULL LOAD</b>	
To exhaust system	/
To water and oil	/
Radiated to room	/
To charge cooler	/



## ALTERNATOR

SYNCHRONOUS, THREE-PHASE, SELF-EXCITED, SELF-REGULATED	
Continuous power	11.5 kVA
Stand-by power	12.5 kVA
Three phase voltage	380 ÷ 415 Vac
Frequency	50 Hz
Cos φ	0.8
Model A.V.R.	HVR 10
Voltage regulation acc.	± 1 %
Sustained short circuit current	≤ 3 In
Transient dip (100% load)	< 15 %
Recovery time	/
Efficiency at 100% load	83.5 % (400V - Cos φ 0.8)
Insulation	Class H
Connection - Terminals	Star - N°6
Electromagnetic compatibility (R.F.I. suppr.)	/
Waveform distortion - THD	< 4 %
Telephone interference - THF	/

REACTANCES (11.5 KVA - 400V)	
Direct axis synchronous - Xd	239 %
Direct axis transient - X'd	19 %
Subdirect axis transient - X''d	4,6 %
Quadrature axis synchronous - Xq	130 %
Quadr. axis subtransient - X''q	/
Negative sequence - X2	/
Zero sequence - X0	/
TIME CONSTANTS	
Transient - T'd	0,046 sec
Subtransient - T''d	0,006 sec
Open circuit - T'do	0,58 sec
Armature - Ta	/
Short-circuit ratio Kcc	0.72
IP protection degree	IP 23
Cooling air flow	0.082 m³/sec.
Coupling   Bearing	Direct SAE 5 - 7 ½ - N°1

## GENERAL SPECIFICATIONS

Fuel tank capacity	38 lt.
Running time (75% to PRP)	14.5 h
Starter battery	12 Vdc -37Ah / 330A CCA(EN)
IP protection degree	IP 23

* Measured acoustic power LwA (pressure LpA)	91.8 dB(A) (66.5 dB(A) @ 7m)
* Guaranteed acoustic power LwA (pressure LpA)	93 dB(A) (68 dB(A) @ 7m)
Performance class	G1

\* Acoustic power in accordance with Directive 2000/14/EC



# CONTROL PANELS

## AUTOMATIC MANUAL CONTROL PANEL

- Controller IntelliNano Plus
- Supply switch
- Engine protection circuit breakers :1x30A - 1 x 16A
- Emergency stop button
- Siren
- TCM 35 remote control plug
- PAC (ATS) plug 16 poles (Automatic control panel only)
- Battery charger (Automatic control panel only)
- Fuses: 3x 2A
- Circuit breaker
- Earth leakage circuit breaker (GFI)
- Output sockets: 1x 400V 16A 3P+N+T CEE IP 67  
1x 230V 16A 2P+T CEE IP 67  
1x 230V 16A 2P+T Schuko
- Earth terminal (PE)



INTELINANO PLUS CONTROLLER CHARACTERISTICS	
Operating mode	<ul style="list-style-type: none"> <li>• MAN.- AUTO</li> </ul>
Display	<ul style="list-style-type: none"> <li>• Graphic back-light LCD display 128x64 pixels</li> </ul>
LEDs	<ul style="list-style-type: none"> <li>• Engine operation</li> <li>• AUTO operating mode</li> <li>• Alarm</li> </ul>
Buttons	<ul style="list-style-type: none"> <li>• START button</li> <li>• STOP button</li> <li>• AUTO button</li> <li>• N° 2 buttons for controller programming</li> </ul>
Generator Measures	<ul style="list-style-type: none"> <li>• Voltage : L1-L2 / L2-L3 / L3-L1 - N-L1/N-L2/N-L3 (L1-L2 with AUTOMATIC panel)</li> <li>• Current : I1</li> <li>• Powers : kVA</li> <li>• Frequency</li> </ul>
Engine Measures	<ul style="list-style-type: none"> <li>• Water temperature (optional)</li> <li>• Oil pressure (optional)</li> <li>• Fuel level</li> <li>• Rpm meter</li> <li>• Battery voltage</li> <li>• Maintance</li> <li>• Hours meter</li> </ul>
Generator Protections	<ul style="list-style-type: none"> <li>• Short circuit</li> <li>• Over-Udervoltage</li> <li>• Over-Uderfrequency</li> <li>• Phase sequence</li> </ul>

Engine Protections	<ul style="list-style-type: none"> <li>• Overspeed</li> <li>• High water temperature warning</li> <li>• Low oil pressure warning</li> <li>• Low fuel level warning</li> <li>• Under battery voltage</li> <li>• Battery charge alternator failure</li> <li>• Start failure</li> <li>• Stop failure</li> <li>• Emergency stop</li> </ul>
AMF functins (Automatic control panel only)	<ul style="list-style-type: none"> <li>• Measure mains voltage : L1-L2 / L2-L3 / L3-L1 - N-L1 / N-L2 / N-L3</li> <li>• Measure mains frequency</li> <li>• Three phase detection</li> <li>• Over-Under mains voltage</li> <li>• Over-Under mains frequency</li> <li>• Phase sequence</li> </ul>
Features	<ul style="list-style-type: none"> <li>• Event log and alarms (10 events)</li> <li>• Operator interface with icons, no text</li> <li>• Remote Start and Stop</li> <li>• Pre-heating</li> <li>• Fully programmable from the panel or from PC</li> <li>• Direct connection to engines with ECU via Can bus J1939</li> <li>• Manual operation (MRS) with remote start</li> <li>• IP65 protection</li> <li>• Operation temperature: -20°C / +70°C</li> </ul>
Communication	<ul style="list-style-type: none"> <li>• Setup USB port</li> <li>• CAN BUS interface (J1939 only)</li> </ul>



# WEIGHT - DIMENSIONS AND ACCESSORIES

GE SX-11000 KDT




### DRY WEIGHT MACHINE:

- 340 Kg

Generating set pictured may include optional accessories.



### DIMENSIONS DRAW (mm)



### OPTIONS ON REQUEST

- Load transfer switch (ATS) PAC 17 (25A) (Only with automatic control panel)
- Load transfer switch (ATS) PAC I 42 809ATS (60A)
- Remote control TCM35
- Trolley CTM255
- Site tow CTL255
- Road trailer CTV4
- Earthing



### VERSIONS ON REQUEST

- Version with automatic panel



### FACTORY INSTALLATION OPTIONS

- Gauges - water temperature and oil pressure
- Engine heater
- Main battery switch
- Isometer
- Radio control

## GENERAL INFORMATION

### COMPLIANCE GENERATING SETS WITH EC DIRECTIVES AND STANDARDS

- 2006/42 / EC (Machines Directive)
- 2014/35 / EU (Low Voltage Directive)
- 2014/30 / EU (EMC Directive)
- 2000/14 / EC (Directive Acoustic Emission for machines for use outdoors)
- ISO 8528 (Reciprocating internal combustion engine driven alternating current generating sets)



ISO 9001:2015 - Cert. 0192

### WARRANTY

All devices are covered by the manufacturer's warranty.

The company reserves the right to change this specification without notice. For further information please contact the sales department.

© MOSA - Viale Europa, 59 - 20090 Cusago (Milano) - Italy - phone +39-0290352.1 - fax + 39-0290390466 E-mail: info@mosa.it Web site: www.mosa.it

