







GENERATING SET GE 1500 RED STAR

■ MOSA gasoline engine in compliance with EC-II and EPA&CARB

- Oil alarm shut off
- Single-phase synchronous alternator
- Overload protection
- Battery charger 12V 8.3A
- Silenced
- Portable
- In compliance with CE directives for noise and security





















Options on request Plug 230V 16A 2PT (M) SCHUKO

Earthing Kit MT 10



Technical Data

GE 1500 RED STAR

A.C. GENERATION 50 Hz, synchronous, single-phase, self-excited, self-regulated, brushless

Single-phase generation (max) 1.3 kW / 230V / 5.6 A Single-phase generation (continuous) 1.1 kW / 230V / 4.7 A

Battery charger d.c. 8.3A **Duty cycle** 100% Power factor (Cos φ) 1 Insulation class H

ENGINE Gasoline, 4-stroke, air cooled

Type MOSARS 90 Output 2.2 kW (3.0 HP)

Displacement 90 cm3 Cylinders

Fuel consumption 337 g/kWh

GENERAL SPECIFICATIONS

5.5 I Tank capacity Runnig time 5 h Protection IP 21 **Dimensions Lxlxh**

455x377x365 Weight 25 kg ~

Measured acoustic power 91 LWA (66 dB(A) - 7 m) Guaranteed acoustic power 92 LWA (67 dB(A) - 7 m)