

## GENERATING SETS GE 7500 HSX (EAS)

- Honda OHV gasoline engine
- Engine protection (oil)
- Three-phase synchronous alternator
- Circuit breaker / GFI - ELCB
- Sockets EEC: 1x400V/16A 3P+N+T - 1x230V/16A 2P+T
- Prepared for connection to Automatic transfer unit
- Meets EEC directives



Standard equipment										
	Gasoline engine	Air cooling	Electric starter	Battery 12V	Engine shut down (oil)	Hour counter	Low fuel indicator	Bat.-charge thermal	Ready for EAS/TCM	Start local / Remote selector
Options on request										
	Synchronous alternator	Compound	Voltmeter	EEC sockets	Circuit breaker	Ground fault interrupter				
	● Plugs 400/230V			● Automatic transfer unit EAS15B-806			● CTM7 (4 wheels)			
				● Earthing Kit MT10						
				● Kit exhaust extension						

### Technical Data

### GE 7500 HSX (EAS)

<b>A.C. GENERATION</b>	<b>50 Hz, synchronous, three-phase, self-excited, self-regulated, brushless</b>
Three-phase power (max)	7.5 kVA (6 kW) / 400 V / 10.8A
Three-phase power (continuous)	6.5 kVA (5.2 kW) / 400 V / 9.4A
Single-phase power	4 kVA (4 kW) / 230 V / 17.4A
Duty cycle	100%
Cos φ	0.8
Insulation class	H
On request other voltages and frequencies (60 Hz)	

<b>ENGINE</b>	<b>Gasoline, 4-stroke, air cooled</b>
Type	HONDA GX 390
Net power	7.7 kW (10.3 HP)
Speed	3000 rpm
Displacement	389 cm <sup>3</sup>
Cylinders	1
Fuel consumption (Load 75%)	2.15 l/h - 313 g/kWh

<b>GENERAL SPECIFICATIONS</b>	
Tank capacity	20 l
Running time (Load 75%)	9.5 h
Protection	IP 23
Dimensions Lxwxh (mm) *	1060x570x665
Weight *	165 kg
Measured acoustic power **	88 LWA (63 dB(A) - 7 m)
Guaranteed acoustic power **	89 LWA (64 dB(A) - 7 m)

\* Dimensions and weight are inclusive of all parts without optional CTM \*\* Acoustic power according to 2000/14/CE

**Values shown are nominal values. For further information please contact the sales department.**